# tara<sup>™</sup> whirlpool bath and soaking bath with integral skirt



like the fabled Irish tower of kings that shares its name, the tara™ whirlpool bath is itself a singularly regal experience in an everyday world.







Cozy up to the Tara<sup>™</sup> whirlpool bath's corner configuration and linger as you massage away the cares of the day.

### features:

- 4 Fully adjustable TheraPro<sup>™</sup> jets
- 2 Directionally adjustable AccuPro™ lumbar jets
- 1 Directionally adjustable AccuPro™ foot jet
- Exclusive Tru-Level<sup>™</sup> base system
- Slip-resistant bottom
- Patented Silent Air™ Induction system
- Integral skirt
- Drain included on whirlpool baths

# tara<sup>™</sup> whirlpool bath with integral skirt

model number: N820 RH Pump

exterior dimensions:

60" long x 60" wide x  $20\frac{3}{4}$ " high

interior dimensions (at bottom): 45" long x 40" wide

# of Jets/type of Jets:

4 TheraPro<sup>™</sup> Jets,

2 AccuPro™ Lumbar Jets,

1 AccuPro<sup>™</sup> Foot Jet

operating gallons: **74 gallons** 

tara<sup>™</sup> soaking bath with integral skirt

model number: N821

exterior dimensions:

60" long x 60" wide x 203/4" high

interior dimensions: 45" long x 40" wide

**Detail:** The Tara™ whirlpool bath places Jacuzzi's Magic Touch® controls right in reach. Perfectly positioned AccuPro™ jets massage away cares as you recline against Tara's backrest.



# Tara<sup>™</sup> Corner Whirlpool Bath w/Integral Skirt



# Tara<sup>™</sup> Corner Bath with Integral Skirt

Model: N821

Model: N820

# **Ordering Information**

Product Code:
N821 Tara™ Corner Bath
w/Integral Skirt
N820 Tara™ Corner Whirlpool Bath
w/Integral Skirt Right Hand

- Center Drain Location
- · Accessories / Hardware:

Trip-Lever Drain Kit #X559 Rotary Drain Kit, 26" Cable #8730 4 X HTC Jet Trim Kit: #D095 2 X BMH Jet Trim Kit: #J869

• Trim Kit Finishes Available:

(827) - Chrome

(898) - Brushed Chrome

(815) - Satin Nickel

(829) - Bright Brass

(805) - Platinum

(826) - Brushed Nickel

(849) - Oil Rubbed Bronze

# 60" | Motor | 14" x 4" | 27-1/4" | 35" | 44" | 35" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 44" | 4

### **Installation Notes**

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Electrical Components and Electrical Specifications do not apply to non-jetted baths.

## **Technical Specifications**

### **Dimensions**

60" L x 60" L x 20-3/4" H (1524 mm) L x (1524 mm) L x (527 mm) H

### **Drain/Overflow**

A: 16" (406 mm) B: 12-3/8" (314 mm)

### Cutout

NΙΑ

### **Total Weight**

N820: 999 lb (453 kg) / 40 lb/sq. ft. (195 kg/m<sup>2</sup>) N821: 957 lb (434 kg) / 38 lb/sq. ft. (187 kg/m<sup>2</sup>)

### **Operating Gallonage**

74 U.S. Gal. (280 Liters) 87 U.S. Gal. (329 Liters)

### **Product Weight**

N820: 133 lb (60 kg) N821: 91 lb (41 kg)

### **Skirt Mounting**

Integral

### Electrical Specifications Model N820 only Requires a dedicated GFCI protected separate circuit.

Motor/Pump: 120 VAC, 15 AMP, 60 Hz. RapidHeat $^{TM}$ : 120 VAC, 15 AMP, 60 Hz.

### Heater (Optional) Model N820 only Requires a dedicated GFCI protected separate circuit.

RapidHeat™: P/N S750000

Product Shown: Tara  $^{TM}$  Corner Whirlpool Bath with Integral Skirt Model: N820

<sup>\*</sup> Measurements inside unit represent cutout in floor to allow for drain/overflow.





